

has performed a number of scopes in Australia.

supply requirements. The vessel's dynamic positioning provides ideal manoeuvrability for working alongside offshore facilities and its cargo capacity provides reliable supply support.

### Contact MMA Offshore

#### Australia

Head Office

Level 10 12-14 The Esplanade Perth WA 6000

Ph: +61 8 9431 7431 Fax: +61 8 9431 7432

#### South East Asia

Singapore Office

9 Raffles Place, #15-02 Republic Plaza Singapore 048619

Ph: +65 6265 1010 Fax: +65 6864 5555

## United Kingdom

Aberdeen Office

30 Abercrombie Court Prospect Road, Arnhall Business Park Westhill Aberdeenshire United Kingdom AB32 6FE

Ph: +44 1224 659950 Fax: +44 1224 659951

# MMA Coral

**Anchor Handling Tug Supply** 



General		Dimensions	
Official No	397095	LOA	70.05 m
Call Sign	9V9448	Breadth - moulded	17 m
IMO No	9594200	Depth - moulded	7.5 m
Year Built	2011	Draft	6.1 m
Port of Registry	Singapore	GRT	2,763 T
Flag	Singapore	NRT	829 T
Class	American Bureau of Shipping	Deadweight	2,400 T
Notation		Free Deck Area	500 m <sup>2</sup>
	Vessel (AH), Fire Fighting Vessel Class 1, Towing Vessel, *AMS, *DPS-2	Deck Strength	7.5 T/m²

MMAOFFSHORE.COM



# MMA Coral

# **Anchor Handling Tug Supply**



ВНР	8,000
Knots	14
Knots	10
T	108
	Knots

Tank Capacity		
Fuel Oil	m³	700
Fresh Water	m³	514
Potable Water	m³	500
Foam	m³	15
Ballast Water	m³	1,336
Liquid Mud	m³	382
Cement	m³	200
Dispersant	m³	15
Dry Bulk	m³	(refer to cement)
Methanol	m³	NÁ

Discharge Rates	
Fuel Oil	1 x 117 m <sup>3</sup> /hr @ 80 m head
Fresh Water	1 x 120 m <sup>3</sup> /hr @ 90 m head
Ballast / Drill Water	1 x 120 m <sup>3</sup> /hr @ 75 m head
Potable Water	1 x 120 m <sup>3</sup> /hr @ 90 m head
Dry Bulk	2 x 20 m <sup>3</sup> /hr @ 5.5 Bar
Liquid Mud / Brine	2 x 75 m <sup>3</sup> /hr @ 95 m head

Machinery / Propulsion	
Main Engines	2 x MAK 9 M 25, 4,000 BHP
Bow Thruster	2 x 600 kw Tunnel Type
Stern Thruster	1 x 600 kW Tunnel Type
Generators	2 x Volvo Penta 350 kW
Emergency Generators	1 x Volvo 122 kW
Propulsion	2 x CPP in Kort Nozzle

Emergency Generators	1 x Volvo 122 kW
Propulsion	2 x CPP in Kort Nozzle
Deck Equipment	
Crane	1 x 2T Electro- Hydraulic Telescopic Palfinger Crane
Capstan	2 x 5 tonne Electro- Hydraulic; Brattvaag
Towing Winch	1 x Electro-Hydraulic Waterfall Double Drum Waterfall
Capacity	2 x 400 mm x 450 mm
Wire Capacity	58 mm x L 1400 m
Brake Holding	250 T
Anchor Handling Winch	1 x Electro-Hydraulic Waterfall Double Drum Waterfall
Capacity	2 x 400 mm x 450 mm
Wire Capacity	58 mm x L 750 m
Brake Holding	250 T
Shark Jaw	1 x 250 tonne Karmfork
Towing Pin	2 x 200 tonne Electro- Hydraulic
Tugger Winch	2 x Electro-Hydraulic (SWL 12 MT)
Wire Capacity	2 x 406/900 x L 500 mm
Brake Holding	10 T
Stern Roller	2,200mm x L4, 800 mm (250 tonnes capacity)
Deck Voltage & Sockets - Quantity & Voltage	2 x 440 V and 2 x 220 V

Rescue & Fire Fighting	
FRC	1 x Harding FRB-
	650
Daughter Craft	Nil
FiFi Class	Class 1
Dynamic Positioning	
DP - System	DP2
DGPS - Quantity	2 x GLONASS
Fanbeam - Quantity	1 x CyScan
	.,
Accommodation	
	Qty
Cabin (4 Berth)	Nil
Cabin (2 Berth)	20
Cabin (Single Berth)	10
Total Accommodation	50 Pax
Communication Equipment	
	Qty
Navtex Receiver	1
AIS	1
Watch Alarm	1

2 x VHF, 1 x MF/HF

Qty
1
1
1
2
1
2 x 5 m³/day



SSB Intercom Inmarsat-C EPIRB

GMDSS VHF Radio (MF/HF)

GMDSS Handheld VHF