

### Contact MMA Offshore

Australia

Head Office

Level 10 12-14 The Esplanade Perth WA 6000

Ph: +61 8 9431 7431 Fax: +61 8 9431 7432

#### South East Asia

Singapore Office

9 Raffles Place, #15-02 Republic Plaza Singapore 048619

Ph: +65 6265 1010 Fax: +65 6864 5555

### United Kingdom

Aberdeen Office

30 Abercrombie Court Prospect Road, Arnhall Business Park Westhill Aberdeenshire United Kingdom AB32 6FE

Ph: +44 1224 659950 Fax: +44 1224 659951

## MMA Majestic

**Anchor Handling Tug Supply** 



General		Dimensions	
Official No	900092	LOA	78.2 m
Call Sign	9WNJ8	Breadth - moulded	18.5 m
IMO No	9657935	Depth - moulded	8 m
Year Built	2014	Draft	6.6 m
Port of Registry	Labuan	GRT	3,607 T
Flag	Malaysia	NRT	1,332 T
Class	American Bureau of Shipping	Deadweight	3,500 T
		Free Deck Area	580 m <sup>2</sup>
Notation	Fire Fighting Vessel Class 1, Offshore Support Vessel, SPS, (E), *AMS, *ACCU, *DPS-2, BP 160.7 tonne, SPS	Deck Strength	5.5 T/m²

MMAOFFSHORE.COM



# MMA Majestic

### Anchor Handling Tug Supply



Performance		
BHP	BHP	12,070
Speed - Maximum	Knots	12
Speed - Economical	Knots	8
Bollard Pull	T	160.7

Tank Capacity		
Fuel Oil	m³	1,197.1
Fresh Water	m³	316
Potable Water	m³	316 (same as FW)
Foam	m³	23.3
Ballast Water	m³	1,723 / 450 (DW)
Liquid Mud	m³	791
Cement	m³	179.4
Dispersant	m³	23.3
Dry Bulk	m³	330.8 (incl 2 cement Tk.)
		,

Dioonargo natoo	
Fuel Oil	2 x 200m³/hr @ 90 m head
Fresh Water	1 x 150m <sup>3</sup> /hr @ 90 m head
Ballast / Drill Water	1 x 200m <sup>3</sup> /hr @ 90 m head
Potable Water	1 x 150m <sup>3</sup> /hr @ 90 m head
Dry Bulk	2 x 25m <sup>3</sup> /hr @ 8 bar
Liquid Mud / Brine	2 x 75m <sup>3</sup> /hr @ 240 m head

Machinery / Propulsion	
Main Engines	2 x Wartsila 9L 32, 4,500 kW
Bow Thruster	2 x 600 kW Tunnel Type
Stern Thruster	2 x 600 kW
Generators	2 x Caterpillar 550 kW
Emergency Generator	1 x 95 ekW @ 1,800 rpm
Propulsion	2 x CPP

Deck Equipment	
Crane	1 x Electro-Hydraulic Telescopic Boom (5 T @ 15 m, 7.5 T @ 5 m)
Capstan	2 x 10 tonne Rolls-Royce Brattvaag
Towing Winch	1 x electro-hydraulic, Waterfall Type, Brattvaag Waterfall
Capacity	300 T @ 0 - 10.2 m/min
Wire Capacity	76 mm x 2000 m
Brake Holding	450 T
Anchor Handling Winch	1 x electro-hydraulic, Waterfall Type, Brattvaag Waterfall
Capacity	300 T @ 0 - 10.2 m/min
Wire Capacity	76 mm x 2,000 m
Brake Holding	450 T
Shark Jaw	2 x 600 tonne Karmfork
Towing Pin	4 x 300 tonne Karmoy Electro-Hydraulic
Tugger Winch	2 x 10 tonne Hydraulic - Brattvaag AKMX4115
Wire Capacity	25 mm x 200 m
Brake Holding	10 T
Stern Roller	4.5 m x 2.3 m (500 tonne capacity)
Deck Voltage & Sockets - Quantity & Voltage	2 x 440v, 2 x 220v

Rescue & Fire Fighting	
FRC	1 x 13 person Jiangyin Xinjiang GJ6.OB-1 RB
FiFi Class	Class 1
Dynamic Positioning	
DP - System	DP-2
DGPS - Quantity Fanbeam - Quantity	∠ Nil
Microwave Reference	Mini Radascan
Accoustic Sensor / HPR	1 x HIPAP (High Precision Accoustic Positioning) - 500
Laser Based System	1 x CyScan MK IV
Accommodation	
Cabin (2 Berth) Cabin (Single Berth) Total Accommodation	Qty 20 6 46 Pax
Communication Equipment	
Navtex Receiver	Qty 1
AIS	1
Watch Alarm	1
SSB	1
Intercom	1
Inmarsat-C	2
EPIRB	1 2 x VHF, 1 x MF/HF
GMDSS VHF Radio (MF/HF)	

real real real real real real real real	
lavigation Equipment	
	Qty
Magnetic Compass	1
Gyro Compass c/w Autopilot	1
GPS Navigator	1
Radar	2
Speed Log	1
Other Equipment	
Vater Maker	2 x 5 m <sup>3</sup> /day

