

The Mermaid Strait has been on continuous hire since its delivery in 2012 to Woodside, providing FPSO offtake support services on the North West Shelf of Western Australia.

Contact MMA Offshore

Australia

Head Office

Level 10 12-14 The Esplanade Perth WA 6000

Ph: +61 8 9431 7431 Fax: +61 8 9431 7432

South East Asia

Singapore Office

9 Raffles Place, #15-02 Republic Plaza Singapore 048619

Ph: +65 6265 1010

United Kingdom

Aberdeen Office

30 Abercrombie Court Prospect Road, Arnhall Business Park Westhill Aberdeenshire United Kingdom AB32 6FE

Ph: +44 1224 659950 Fax: +44 1224 659951

Mermaid Strait

Anchor Handling Tug



General		Dimensions	
Official No	860134	LOA	52.35 m
Call Sign	VJN3713	Breadth - moulded	14.6 m
IMO No	9616216	Depth - moulded	6.25 m
Year Built	2012	Draft	5.3 m (incl. Skeg)
Port of Registry	Dampier	GRT	1,344 T
Flag	Australia	NRT	403 T
Class	American Bureau of Shipping	Deadweight	979 T
	∗A1, Towing Vessel,	Free Deck Area	260 m ²
Notation	(Fire Fighting Capability), Offshore Support Vessel AH, (E), *AMS, *ACCU, *DPS-1, ENVIRO, GP	Deck Strength	5 T/m²

MMAOFFSHORE.COM



Mermaid Strait

Anchor Handling Tug



Performance		
BHP	BHP	7,342
Total kW	kW	5,475
Speed - Maximum	Knots	12.5
Speed - Economical	Knots	8.5
Bollard Pull	T	69
Tank Capacity	3	507

iaiii oapaoiij		
Fuel Oil	m³	587
Fresh Water	m ³	283
Foam	m³	1
Ballast Water	m³	634.6
Discharge Bates		

Discharge Rates	
Fuel Oil	110 m ³ /hr @ 60 m head
Fresh Water	120 m³/hr @ 60 m head
Ballast / Drill Water	120 m³/hr @ 60 m head
Potable Water	120 m³/hr @ 60 m head
Dry Bulk	NA
Liquid Mud / Brine	NA
Dispersant	NA

Machinery / Propulsion	
Main Engines	3 x 1,825 kW Caterpillar 3516B Diesel Electric
Bow Thruster	1 x 550 kW Schottel STT2
Harbour Generator	1x 250 kW Caterpillar CP9
Generator	NA
Emergency Generator	1 x 40 kW Caterpillar Generator
Propulsion	2 x 2,000 kW Schottel SRP 1515 FP, Azimuth

Deck Equipment	
Crane	1 x 1.58 T @ 10.2 m, HIAB TH2.CC.19.0
Capstan	2 x 8 tonne Plimsoll Vertical Hydraulic Capstan
Towing Winch	1 x Plimsoll Double Drum Waterfall - Upper Drum
Capacity	52 mm x 800 m @ 10 layers
Wire Capacity	70 T x 0.85 m/min (low); 15 T @ 0.4 m/min (high)
Brake Holding	200 T (1st layer, static)
Anchor Handling Winch	1 x Plimsoll Double Drum Waterfall - Lower Drum
Capacity	52 mm x 800 m @ 10 layers
Wire Capacity	70 T x 0.85 m/min (low); 15 T @ 0.4 m/min (high)
Brake Holding	200 T (1st layer, static)
Shark Jaw	1 x 200 tonne Cargotec hydraulic
Towing Pin	1 x 100 tonne Cargotech hrydraulic
Tugger Winch	2 x 10 tonne Plimsoll
Wire Capacity	22 mm x 150 m
Brake Holding	20 T
Bow Winch	1 x Cargotec anchor windlass/towing winch Split Drum
Capacity	35 T
Wire Capacity	52 mm x 800 m SWR + 72 mm x 100 m syn.rope
Brake Holding	150 T
Stern Roller	Cargotec 3 m x 1.5 m (150 tonne capacity)
Deck Voltage & Sockets - Quantity & Voltage	2 x 440 V 60Hz 30A

The righting Equipment	
Fire Monitor Total Capacity	2 2 x 600 m³/hr = 1200 m³/hr
Fire Pump Total Capacity	2 120 m³/hr
Rescue Equipment	
FRC Rescue Zone Dacon Scoop - Quantity	1 x 15 person x Noreq 650 FRC Yes NA
Dynamic Positioning	
DP Model DGPS - Quantity Joystick	DPS-1 Converteam 1 Converteam
Accommodation	
Cabin (2 Berth) Cabin (Single Berth) Total Accommodation	Qty 11 2 24 Pax

Fire Fighting Equipment

Communication Equipment	
	Qty
Navtex Receiver	1
AIS	1
Watch Alarm	1
SSB	1
Intercom	1
Inmarsat-C	2
EPIRB	2
GMDSS VHF Radio (MF/HF)	2 x VHF, 1 x MF/HF
GMDSS Handheld VHF	3
VSAT	1

Navigation Equipment	
Magnetic Compass	Qty 1
Gyro Compass c/w Autopilot	2 x Gyro compass, 1 x autopilot
GPS Navigator	1
Radar	2
Speed Log	1

Specialist Equipment	
Bow Fendering	Cylindrical rubber fendering
Pilot Disembarkation Stations	2
Daughter Craft	No
Oil Dispersant Boom	No
Sewage Treatment Unit	1 (MARPOL Compliant) + Holding Tank
Water Maker	5 m³/day

